

RiverGarden

SOLUÇÃO DE VIDEOCONFERÊNCIA



LifeSize® Room 200™

Introducing Full HD for the most realistic video communications experience ever



Experience Superior Communication

Experience the world's first, Full HD video communications system. One look and you can see for yourself that the LifeSize® difference is the LifeSize experience - superior video experiences across cities, countries and continents.

With the LifeSize Room 200 solution, you get every bit of quality available today, with Full High Definition, standards-based 1080p30 for the highest available resolution and 720p60 for the best motion handling with lower latency. Plus, an embedded 6-way Continuous Presence multipoint bridge (with 4 visible participants), complete with transcoding and all digital I/O in a compact, sleek unit that's less than half the size of comparable solutions.

Flexibility is enhanced, since our exemplary attention to the human interface ensures that the LifeSize Room 200 system is easy to use. And because we're committed to open architecture, proven LifeSize interoperability provides full integration into your existing communications infrastructure.

You also get unprecedented bandwidth/performance:

- 768kbps for 720p30
- 1.1Mbps for 720p60
- 1.7Mbps for 1080p30

In today's world, better than being there.

In addition to technology, service and support, LifeSize offers the most interactive, face-to-face video communications experience you can get. In fact, the LifeSize Room 200's exceptional quality and user simplicity now make remote communications a more productive, true-to-life experience. And like all LifeSize products, LifeSize Room 200 delivers superior quality of experience, unique flexibility and unmatched price performance.

LifeSize Room 200 Key Features

Video Quality Full High Definition Standards-based 1920x1080 - 30fps 1280x720 - 60fps

HD Monitors



HD Cameras Pan-Tilt-Zoom (PTZ)





HD Audio



External Audio, Video & Data Input/Output

Audio: 4 in, 2 out Video: 6 in, 2 out Data: 1 in, 1 out

Point-to-Point HD Video Communications



Embedded Continuous Presence (CP) HD Multipoint



Embedded Voice Activated Switching (VAS) HD Multipoint



Product Specifications - LifeSize® Room 200™

System Components LifeSize codec with stand High Definition PTZ Lifesize Camera 200 LifeSize Phone Wireless remote control Power Supply Cables

Communications

H.323, SIP

128Kbps - 6.0Mbps (point-point) 128Kbps - 2.0Mbps (multipoint, per call) 1xRJ-45 Network LAN (10/100 Mbps) 1xRJ-45 for LifeSize Phone (PoE supported) 1xRJ-45 for LifeSize Networker (PoE supported) 1xRJ-11 for analog telephone line

1x3.5mm Mic In for LifeSize MicPod

Support for multiple HD displays

Any high definition display supporting HDMI or DVI-I input For additional information on displays, visit: www.lifesize.com/support

High Definition 1080p30/720p60 PTZ Camera

Support for two active camera sources at 720p30 Wide-angle zoom lens with 70 degree field of view 4x Optical zoom

Auto focus / Automatic gain control 10 camera presets (near and far end) Standard 3.0 M HDMI cable Support for Sony EVI-HD1 camera (optional)

Video Specifications/Video Resolutions

Maximum resolutions widescreen 16:9 aspect ratio All resolutions progressive scanning All resolutions at 30 frames per second except 60 frames per second where noted 128Kbps (400x244pixels) Widescreen FCIF 384Kbps (768x432pixels) Cable TV 512Kbps (848x480pixels) DVD resolution 768Kbps(1280x720pixels) High Definition 1.1Mbps (1280x720pixels @ p60) High Definition 1.7Mbps or higher (1920x1080pixels) High Definition

Video Standards

H.261, H.263, H.263+, H.264 and H.239 compliant Support for multiple dual live streaming modes: 1080p30 and 720p5 720p60 and 720p5 720p30 and 720p30

Video Formats

High Definition, 16:9 aspect ratio

Video Inputs (6 Inputs)

1 x High Definition Camera (720p30) 2 x HD Video In (1080p30/720p30)

1 x DVI-I In (VGA enabled)

1 x Component In or 1 x Composite In

1 x S-Video In (VGA enabled)

Video Outputs (2 Outputs)

1 x HD Video Out (1080p30/720p60) 1 x DVI-I Out (1080p30/720p60)

Fully Integrated, HD Audio Conference Phone 100Hz up to 16kHz

Powered by codec directly through cable

Audio Features

High Definition audio GIPS NetEQ packet loss concealment Full duplex for natural conversations Echo cancellation for echo-fee calls Automatic gain control Automatic noise reduction MicPod or Dual MicPod support (optional)

Audio Standards

G.711, G.722, G.722.1 (Polycom© Siren14™), G.728, G.729, MPEG-4 -AAC-LC

Audio Inputs (4 Inputs)

1 x RJ-45 (LifeSize Phone) 2 x Stereo Line In (3.5mm) 1 x Mic In - Two channel (3.5mm)

Audio Outputs (2 Outputs)

1 x RJ-45 (LifeSize Phone) 1 x Stereo Line Output (3.5mm)

Other Supported Standards

H.221, H.224, H.225, H.231, H.241, H.242, H.245, H.281, BONDING (ISO13871), RFC 3261, RFC 3264, RFC 2190,

User Interface & Features

Context sensitive user interface Graphical User Interface Call Manager 14 localized languages supported Do Not Disturb mode

Security

Admin and User level password SNMP security alerts Ability to disable HTTP, SSH and Telnet services H.235 encryption support including strict compliance IEEE 802.1x support Kensington Lock™

Intelligent Network Features

NAT/Firewall Traversal (H.460/SIP) IPv4 and IPv6 support Auto H.323 dialing ISDN support via LifeSize Networker

Directory and Address Book

Up to 1000 local directory entries Save, Lock, Remove Redial List features Missed call notification Auto-Discovery directory lookup (patent pending) LDAP support / H.350 compliant Meetings Directory support

Embedded HD Multipoint Control Unit

6-way HD CP multipoint conference with up to 4 visible

6-way HD VAS multipoint conference

Transcoding support

Virtual Multiway allows participant viewing control (patent pending)

H.239 multipoint support shared from any participant Disable multipoint option

System Management

Out of box setup via web interface and management tool 1 x DB-9 RS-232 port configurable as control

Backup and Restore capability JPEG snapshots through web interface

AC Voltage 100-240V, 50-60 Hz, 2.5A via external power supply



Corporate Headquarters: 901 S. Mopac Expressway Building 3, Suite 300 Austin, Texas 78746 USA

Phone: +1 512 347 9300 Fax: +1 512 347 9301 Email: info@lifesize.com www.lifesize.com

LifeSize Communications Toll-Free Europe 008000 999 09 799

APAC:

LifeSize Communications Hong Kong Phone: +852 8239 3695

Environmental Data

Operating temperature: 0 C (32 F) to 40 C (104 F) Operating Humidity: 15% to 85%, non-condensing Storage temperature: -20 C (-4 F) to 60 C (140 F) Storage humidity: 10% to 90%, non-condensing


Codec Dimensions

Width: 373.9mm (14.72") Depth: 225mm (8.86") Height: 48.3mm (1.9") Weight: 2.24 Kg (4.94lbs)

Regulatory Model Number LifeSize Room 200 = LFZ-015

For additional information: www.lifesize.com/support

Information contained in this document is subject to change without notice. LifeSize® is the registered trademark or trademark of LifeSize Communications Inc. All other trademarks are the property of their respective owners. For patents covering LifeSize® products refer to http://www.lifesize.com/support/legal. © Copyright 2009. All rights reserved. April 2009.



RiverGarden

TECHNOLOGY FOR YOU

RIVERGARDEN Lda.

Pessoa Colectiva e Matriculada nº 510 943 179 Capital Social €10.000

SEDE: Av. do Brasil, nº1, 1º Esq.
7300-068 Portalegre | (+351) 245 203 350
ESCRITÓRIO: Rua do Centro Cultural, nº7-B
1700-106 Lisboa (Bairro Alvalade) | (+351) 211 982 485

Nº REGISTO ANPC: RE-2357/2016/ANPC
Nº REGISTO PRÉVIO SIGESP: 2461
Nº REGISTO IMPIC: 85077
Nº REGISTO APSEI: 446

[geral@rivergarden.pt] [www.rivergarden.pt]